

SAFETY DATA SHEET

MITRE FAST - ADHESIVE

Issued: 04.08.08

Page 1

Revision No: 8

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MITRE FAST - ADHESIVE

Product code: MITRE1, 2, ADH1/5

Use of substance / preparation: Cyanoacrylate adhesives are instant bonding, almost single component adhesives that bond

almost all close fitting smooth surfaces in seconds

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW ENGLAND

Tel: 0044 113 240 3456 Fax: 0044 113 240 0024

Emergency tel: 0044 113 240 3456 (office hours only)

Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes, respiratory system and skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHYL-2-CYANOACRYLATE 70-90%

EINECS: 230-391-5 CAS: 7085-85-0

[Xi] R36/37/38

• HYDROQUINONE <1%

EINECS: 204-617-8 CAS: 123-31-9

[Xn] R22; [Xn] R40; [Xi] R41; [Sens.] R43; [N] R50; [Xn] R68

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause

coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

SAFETY DATA SHEET

MITRE FAST - ADHESIVE

Page 2

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS. If

outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Wash the spillage site with large amounts of water. Absorb into dry earth or sand.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Store in original containers

between +5 and +25°C. Storage outside these paramaters will dramatically reduce shelf life and

invalidates all product warrenties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ETHYL-2-CYANOACRYLATE

WEL (15 min STEL): 1.5 mg/m3

HYDROQUINONE

WEL (8 hr TWA): 0.5 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is

above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

MITRE FAST - ADHESIVE

Colourless

Odour: Perceptible odour

Evaporation rate: Negligible **Solubility in water:** polymerises

Also soluble in: Acetone. Most organic solvents.

Viscosity: Viscous
Viscosity value: 1500

Viscosity test method: Brookfield (cps)

Boiling point/range°C: 55

Flash point°C: 180-200 Vapour pressure: <0.2mm/hg

Relative density: 1.05

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Direct sunlight. Moist air.

Materials to avoid: Water. Bases. Alcohols. Amines.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: ETHYL-2-CYANOACRYLATE

ORL RAT LD50 > 5 ml/kg

HYDROQUINONE

ORL MUS LD50 150 mg/kg ORL RAT LD50 720 mg/kg SCU RAT LDLO 300 mg/kg

Chronic toxicity: Vapour is irritating to eyes and mucous membranes above TLV. Prolonged and repeated

exposure to vapour above the established limits may cause allergic reactions with asthma-like

symptoms

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

[cont...]

Issued: 04.08.08

SAFETY DATA SHEET

MITRE FAST - ADHESIVE

Page 4

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R36/37/38: Irritating to eyes, respiratory system and skin.

Safety phrases: S2: Keep out of the reach of children.

S13: Keep away from food, drink and animal feeding stuffs.

S23: Do not breathe vapour.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S46: If swallowed, seek medical advice immediately and show this container or label.

Precautionary phrases: Contains hydroquinone. May produce an allergic reaction.

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

ETHYL-2-CYANOACRYLATE

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R36/37/38: Irritating to eyes, respiratory system and skin.

R22: Harmful if swallowed.

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50: Very toxic to aquatic organisms.

R68: Possible risk of irreversible effects.

SAFETY DATA SHEET

MITRE FAST - ADHESIVE

Page 5

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.