

LUMBERJACK WOOD PRESERVER



Colour	Product Code	Pack Size	Box Qty
Clear	LJCR01	1Ltr	10
	LJCR05	5Ltr	4
	LJCR25	25Ltr	1
Red Cedar	LJRC01	1Ltr	10
	LJRC05	5Ltr	4
Golden Chestnut	LJGC01	1Ltr	10
	LJGC05	5Ltr	4
Fir Green	LJFG01	1Ltr	10
	LJFG05	5Ltr	4
Dark Oak	LJFG05	5Ltr	4

Product Description

LUMBERJACK WOOD PRESERVER is a low solvent, low odour solution based on Micro-fine active technology. The fungicides and algacides present in these formulations are finely dispersed so that wood penetration and hence effectiveness is much greater than standard wood preservation products. In addition the use of ultra light fast pigments on the coloured variants give an even fade resistant finish which will last for years. LUMBERJACK WOOD PRESERVER is fast drying and non flammable; and application to wet timbers is possible without loss of performance. It is specifically designed to deeply penetrate all wood and joinery to give long lasting protection from damage caused by wet rot, dry rot, decay and fungi.

Benefits

- Solvent Free formula
- Non Flammable.
- Internal and external use.
- Can be applied to damp timbers.

Which Type Should I Choose?

Wood Preserver - Clear: For use on interior or exterior rough sawn or planed timber such as floorboards, joists, roof timbers, window frames and doors. This product is an ideal pre-treatment which may be over painted, varnished, or stained when dry (allow 48 hours drying time), but on interior applications, it may also be left as the final finish for a natural wood effect. However, when used externally, over painting/staining is recommended, as this product does not repel water.

Wood Preserver - Fir Green, Dark Oak, Golden Chestnut & Red Cedar: Ideal for general use on rough sawn or planed timber such as window frames, fences, sheds, cladding, horticultural timber, roof timber, joists etc. Fir Green is particularly useful for easy identification of treated timbers and horticultural work. These colours can be over painted, stained or varnished later if required.

Limitations

- Ready to use - do not dilute.
- Always use coarse rather than fine mist generators.
- Do not apply to surfaces on which food is prepared.

- Avoid contact with bitumen, roofing felt or plastics.
- It is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

Surface Preparation

Shake well before use. Apply by brush, spray or dipping. Apply a minimum of two coats if brushing or spraying. The second coat should be applied after the first coat has soaked in but before it is dry. Pay particular attention to thoroughly soaking the end grain. Where possible, dip the end grains of the timber for maximum protection.

Coverage Guide

Joinery, floorboards, roof joists etc: Apply 1 litre of product per 3 - 4m² of surface.

Ideally this should be applied as 2-3 even coats leaving at least 2 hours between applications or dip for three minutes.

Timber not in ground contact: 3 coats by brush or spray or dip for 10 minutes. Coverage: 4m² per litre.

Timber in ground contact: Soak for 1 hour. Coverage: 40 litres per cubic meter.

Health & Safety

See MSDS for full list of hazards.

Storage

Store at moderate temperatures in original containers away from children.

Shelf Life

Use within 2 years of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.