

PVC-U Beads

An alternative range of impact resistant drylining & wet plaster beads for internal or external use.

PVC Plaster Beads are designed for use externally where galvanised beads cannot be used or where they are preferred to stainless steel. They are also used internally in high moisture content areas or where pro-longed drying out periods may be necessary.

Other benefits include:

- Simple installation (with plaster dabs or stainless steel fixings)
- No sharp edges, and safe to handle
- Easy to cut (by use of tin snips or fine tooth saw)
- Non corrosive.

PVC Bead is supplied as standard in white, although many colours are available upon request by supplying us with the relevant 'RAL' reference code.

PVC-U Angle Bead / Thin Coat Angle Bead

Description and Application

PVC-U Angle bead is for use on all plastered and rendered corners, where a true sharp corner is required. It protects the plaster at its most vulnerable point.

Different sizes available for various plaster / render thickness.

PVC-U Thin coat angle bead is used to provide a true sharp corner on plasterboard corner joints or for any smooth background and again protects the plaster at its weakest point.



PVC-U Angle Bead comes in 50 lengths per box for 2/3mm; 50 lengths per box for 6/10mm; 40 lengths per box for 8/12mm and 30 lengths per box for 13/19mm.

Code	Description	Length (m)	Size (mm)
TLPAB23	PVC-U Angle Bead	2.5	2 / 3
TLPAB610	PVC-U Angle Bead	2.5	6 / 10
TLPAB812	PVC-U Angle Bead	2.5	8 / 12
TLPAB1319	PVC-U Angle Bead	2.5	13 / 19

All PVC Beads are available in alternative colours, namely; black, grey, ivory, terracotta and brown as shown here.

