

Ceresit

153A

Technical Datasheet

Version 11.05.2012

Pages 2

PROPERTIES

- ▶ Solvent based adhesive **ACTIVATOR** for use with *Ceresit 153*
- ▶ Reduces fixing times and expands the gap fill of *Ceresit 153* cyanoacrylate adhesive
- ▶ Ensures excess adhesive is fully cured
- ▶ Reduces odour and blooming
- ▶ Fast acting, low viscosity
- ▶ Low odour
- ▶ Ideal for PVCu window trim bonding

APPLICATIONS

For use with *Ceresit 153* cyanoacrylate adhesive for:

- PVCu window trim bonding
- Production lines, such as electronics assembly

PROCESSING

Spray a small quantity of **Ceresit 153A Activator** onto one substrate only and allow solvent to evaporate.

Apply *Ceresit 153 Cyanoacrylate Adhesive* to the other substrate and bring together immediately. Hold for 8 to 10 seconds. Curing will occur almost instantly.

Take precautions not to spray activator near unused cyanoacrylate adhesive, as this will cure off.

Ceresit 153A Activator is especially recommended for use on porous materials, or when ambient temperatures are low.



CHARACTERISTICS

Type :	Contains active components dissolved in a hydrocarbon solvent
Appearance:	Colourless
Flash point:	0°C
Density:	0.79 g/ml
Toxicity:	Low
Viscosity:	1 mPas at 20°C
Aerosol Propellant:	Propane/Butane

IMPORTANT ADVICE**Cleaning of the skin**

During application, wear skin protection

Storage

Keep containers in a cool, well-ventilated area.

Ceresit 153A Activator is a very volatile, extremely flammable liquid.

Keep away from any source of ignition such as heat, sparks and open flames - NO SMOKING.

Shelf Life

Ceresit 153A Activator has a shelf life (stored below +25°C) of 12 months minimum, when stored in original, unopened packaging.

SAFETY**Safety Advice**

PRIOR TO USE: consult the **Safety Data Sheet** (MSDS) for Ceresit 153A Activator.

www.ceresit.co.uk

HIGHLY FLAMMABLE

Keep away from sources of ignition - NO SMOKING

Take precautionary measures against static discharges

Avoid contact with skin and eyes

Work only in a well ventilated area

Wear suitable protective clothing and respiratory protection

Keep out of reach of children

Avoid inhalation of vapours, spray or mist

Wash thoroughly after use

Keep container in a well-ventilated place

Do not empty into drains

Do not puncture or incinerate can

COLOURS

Colourless

PACKAGING

Ceresit 153A is supplied in 150ml aerosol cans

DISPOSAL**Product and packaging disposal**

Do not pour directly into drains. Retain the product for later use, or if beyond shelf life, dispose of the product in accordance with local regulations. Dispose of the empty packaging in accordance with local regulations (please refer to Safety Data Sheet for more information).

Please note: The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control, we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation; except for cases we are liable of gross negligence or false intention.

Henkel AG & Co. KGaA - 40191 Düsseldorf, Germany

www.ceresit.co.uk

