

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

Page 1 Issued: 9/9/08 Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product nameIUMBERJACK TRIPLE ACTION WOOD TREATMENTProduct codeIUN - ALL SIZESUse of substance / preparationTimber PreservativeCompany nameEVERBUILD BUILDING PRODUCTS LTDBITE 41, KNOWSTHORPE WAYCROSS GREEN INDUSTRIAL ESTATELEEDSWEST YORKSHIRELS9OSWENGLANDFire: 0044 113 240 3456Fire: 0044 113 240 3456 (office hours only)Eineir: pault@everbuild.co.ukEnergency tel: 0044 113 240 3456 (office hours only)

2. HAZARDS IDENTIFICATION

Main hazards: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients:	PROPICONAZOLE <1%		
	EINECS: 262-104-4 CAS: 60207-90-1		
	[Xn] R22; [Sens.] R43; [N] R50/53		
•	M-PHENOXYBENZYL		
	3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE <1%		
	EINECS: 258-067-9 CAS: 52645-53-1		

[Xn] R20/22; [Sens.] R43; [N] R50/53

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

Page 2

Ingestion:	Wash out mouth with water.		
Inhalation:	Consult a doctor. Remove casualty from exposure ensuring one's own safety whilst doing so.		
5. FIRE-FIGHTING MEASURES			
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used.		
Exposure hazards:	In combustion emits toxic fumes.		
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin		
	and eyes.		
6. ACCIDENTAL RELEASE MEASURES			
Personal precautions:	Refer to section 8 of SDS for personal protection details.		
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.		
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by		
	an appropriate method.		
7. HANDLING AND STOL	RAGE		
Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.			
	Do not handle in a confined space. Avoid direct contact with the substance.		
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed.		
Suitable packaging:	Must only be kept in original packaging.		
8. EXPOSURE CONTROL	LS / PERSONAL PROTECTION		
Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure all engineering measures mentioned in		
	section 7 of SDS are in place.		
Respiratory protection:	Respiratory protective device with particle filter. Gas/vapour filter, type A: organic vapours		
	(EN141). if spraying		
Hand protection:	Protective gloves.		
Eye protection:	Safety glasses. Ensure eye bath is to hand.		
Skin protection:	Protective clothing.		
9. PHYSICAL AND CHEM	AICAL PROPERTIES		
State:	Liquid		
Colour	Various		

Colour:	Various
Odour:	Barely perceptible odour
Evaporation rate:	Moderate
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Soluble
Also soluble in:	Most organic solvents.
Viscosity:	Non-viscous
Viscosity value:	<5cSt

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

Boiling point/range°C:	approx 100°C
Flash point°C:	>60
Vapour pressure:	4.6
Relative density:	1.00-1.01
pH:	6.5-8.5
VOC g/l:	0

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions. Stable at room temperature.
Conditions to avoid:	Heat. Direct sunlight.
Materials to avoid:	Strong oxidising agents. Strong acids.
Haz. decomp. products:	In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients:	M-PHENOXYBENZYL
	3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE
	ORL MUS LD50 424 mg/kg
	ORL RAT LD50 383 mg/kg
	SKN RAT LD50 1750 mg/kg
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Readily absorbed into soil.	
Biodegradable.	
No data available.	
Very toxic to aquatic organisms.	

13. DISPOSAL CONSIDERATIONS

Disposal operations:	Dispose of according to local or national legislation	
Disposal of packaging:	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.	
NB:	The user's attention is drawn to the possible existence of regional or national regulations	
	regarding disposal.	

14. TRANSPORT INFORMATION

ADR / RID			
UN no:	3082	ADR Class:	9
Packing group:	III	Classification code:	M6
Shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.		
Labelling:	9	Hazard ID no:	90
	, dh,		[cont]

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

IMDG / IMO **UN no: 3082** Class: 9 EmS: F-A,S-F Packing group: III Marine pollutant: . Labelling: 9 IATA / ICAO **UN no: 3082** Class: 9 Packing group: III Packing instructions: 914 Labelling: 9 **15. REGULATORY INFORMATION** Hazard symbols: Dangerous for the environment. Risk phrases: R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Safety phrases: S29: Do not empty into drains. S61: Avoid release to the environment. Refer to special instructions / safety data sheets. S2: Keep out of the reach of children. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28: After contact with skin, wash immediately with plenty of soap and water. S36/37/39: Wear suitable protective clothing, gloves and eye / face protection. **Precautionary phrases:** Use biocides safely. Always read the label and product information before use. Contains propiconazole, m-phenoxybenzyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate. May produce an allergic reaction. M-PHENOXYBENZYL 3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions. **16. OTHER INFORMATION**

Other information: HSE No. : 8529

Risk phrases used in s.3: R22: Harmful if swallowed.

Page 4

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

 R43: May cause sensitisation by skin contact.

 R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

 R20/22: Harmful by inhalation and if swallowed.

 Legal disclaimer:

 The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.