

SAFETY DATA SHEET

206 STRIKE RELEASE OIL

Issued: 3/8/09

Page 1

Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 206 STRIKE RELEASE OIL

Product code: STRIKE - ALL SIZES

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW ENGLAND

Tel: 0044 113 240 3456 Fax: 0044 113 240 0024

Emergency tel: 0044 113 240 3456 (office hours only)

Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

Other hazards: Product is not classified as flammable (R10) due to flashpoint >61°C. This product will however

readily support combustion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: REFINED MINERAL OIL 70-90%

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult

a doctor.

Inhalation: Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

Exposure hazards: In combustion emits toxic fumes.

Issued: 3/8/09

SAFETY DATA SHEET

206 STRIKE RELEASE OIL

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade

immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the

escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method. Do not use equipment in clean-up procedure which may produce

sparks.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of

ignition. Store in original containers between +5 and +25°C. Storage outside these paramaters

will dramatically reduce shelf life and invalidates all product warrenties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: REFINED MINERAL OIL

WEL (8 hr TWA): 5mg/m3 WEL (15 min STEL): 10mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is

above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colourless

Odour: Aromatic

Evaporation rate: Moderate

Solubility in water: Not miscible

Viscosity: Non-viscous

Flammability limits %: lower: 0.6

upper: 7.0

Flash point°C: 61

Autoflammability°C: >61°C

[cont...]

Page 2

Issued: 3/8/09

SAFETY DATA SHEET

206 STRIKE RELEASE OIL

Page 3

Relative density: 0.67

pH: n/a

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: REFINED MINERAL OIL

ORL RAT LD50 > 2 g/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Only slightly biodegradable. Estimated to be approx. 60% over 21 days (CEO L -33-T-62)

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S23: Do not breathe vapour.

206 STRIKE RELEASE OIL

S28: After contact with skin, wash immediately with plenty of soap and water.

S29: Do not empty into drains.

S46: If swallowed, seek medical advice immediately and show this container or label.

Water hazard class: 2

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.